

Tire Size	Pattern	Star Rating	Load Index	TRA Code	Tread Depth (mm)	Type	Standard Rim	Max Load (Kg)	Inflation Pressure (bar)	Max Speed (km/h)
12.00R24	SMS+	★★	175	L-5S	55	TT	8.50-1.3	6900	8.25	25
12.00R24	LGDN	24PR	160	E-3	30	TT	8.5	4000	8.5	50
12.00R24	M08S	★★	178	IND-4	41.5	TL	8.5	7500	10	25
13.00R25	LOFN	★★★★	167	E-3	28.0	TT	8.5	7000	12	50
14.00R24	B03S	★★★★	168	E-4	38	TT	10.0	6050	8	50
14.00R24	LOFN	★★★★	168	E-3	28.0	TT	10.0	10000	12	50
14.00R24 (385/95R24)	B05N	★★★★	170	E-2	23	TL	10.00W	6000	10	70
14.00R24 (385/95R24)	BGZN	★★	170	E-2	23	TL	10.00W	6000	10	70
14.00R24	SMS+									
14.00R24	BWYN	★								
14.00R25	B03S	★★★★	168	E-4	38	TL	10.00/1.5	5600	8	50
14.00R25	LOFN	★★★★	168	E-3	28.0	TT	10.00/2.0 10.00/1.5	10000	12.5	50
14.00R25 (385/95R25)	B05N	★★★★	170	E-2	23	TL	10.00/1.5	6000	10	70
14.00R25 (385/95R25)	BGZN	★★★★	170	E-2	23	TL	10.00/1.5	6000	10	70
14.00R25	BWYN	★★★★	170	E-2						70
14.00R25	LGXN2	★★★★				TT				
14.00R25	LOFN2	★★★★				TT				
14.00R25	LOFN16	★★★★				TT				
14.00R25	LOFN26					TT				
14.00R25	AN609	★★★★				TT				
15.5R25	BWYN	★★★★	176/160	L-2/E-2	25	TL	12.00/1.3	7100/4500	6.5/5.25	10/50
15.5R25	B01N	★★	176/160	L-2/E-2	25	TL	12.00/1.3	7100/4500	6.5/5.25	10/50
16.00R24	BLGN	★★	163	L-2/G-2	27	TL	10.00	4875	3.75	10/40
16.00R25	B02N	★★	177	E-3	34	TL	11.25/2.0	12000	12.5	50
16.00R25	BWYN	★★★★	179	E-2	28	TL	11.25/2.0	6700	10	70

16.00R25	M08S	★★★	200	IND-4	72.5	TL	11.25/2.0	14000	10	25
16.00R25 (445/95R25)	B05N	★★★	174	E-2	28	TL	11.25/2.0	6700	10	70
16.00R25 (445/95R25)	BGZN	★★★	174	E-2	28	TL	11.25/2.0	6700	10	70
17.5R25	B01N	★★	182/167	L-3/E-3	28	TL	14.00/1.5	8500/5450	6.5/5.25	10/50
17.5R25	B01NL	★★	182	L-3	28	TL	14.00/1.5	8500	6.5	10
17.5R25	BWYN	★★	182/167	L-2/E-2	28	TL	14.00/1.5	8500/5450	6.5/5.25	10/50
17.5R25	BWYNL	★★	182/167	L-2/E-3	28	TL	14.00/1.6	8500/5450	6.5/5.25	10/50
17.5R25	SNOWMASTER	★★	182/167	L-2/E-3	29	TL	14.00/1.6	8500/5450	6.5/5.25	10/50
17.5R25	BXDN	★★	182/167	L-3/E-3	28	TL	14.00/1.5	8500/5450	6.5/5.25	10/50
17.5R25	MWS+	★★	182	L-5	68	TL	14.00/1.5	8500	6.5	10
17.5R25	SMS+	★★	182	L-5S	65	TL	14.00/1.5	8500	6.5	10
17.5R25 (445/80R25)	B05N	★★★	170	E-2	28	TL	14.00/1.5	6000	10	70
18.00R25	B03S	★★	185	E-4	47	TL	13.00/2.5	9250	7	50
18.00R25	B06S	★★	185	E-4P	47	TL	13.00/2.5	9250	7	50
18.00R25	SMS+	★★	204	L-5S	80	TL	13.00/2.5	16000	8.25	10
18.00R25	M08S	★★★	214	IND-4	63	TL	13.00/2.5	21200	10	25
18.00R25	B07S	★★★	214	IND-4	63	TL	13.00/2.5	21200	10	25
18.00R25 (505/95R25)	B05N	★★★	186	E-2	28	TL	13.00/2.5	9500	10	70
18.00R33	B06S	★★	191	E-4P	49	TL	13.00/2.5	10900	7	50
18.00R33	BDRS	★★	191	E-4R	54	TL	13.00/2.5	10900	7	50
18.00R33	M08S	★★★	219	IND-4	73	TL	13.00/2.5	24300	10	25
18.00R33	B04S2	★★	191	E-4T	54	TL	13.00/2.5	10900	7	50
18.00R33	B04S	★★								
20.5R25	B01N	★★	193/177	L-3/E-3	31	TL	17.00/2.0	11500/7300	6.5/5.25	10/50
20.5R25	B01NL	★★	193	L-3	31	TL	17.00/2.0	11500	6.5	10
20.5R25	BWYN	★★	193/177	L-2/E-2	31	TL	17.00/2.0	11500/7300	6.5/5.25	10/50
20.5R25	SNOWMASTER	★★	193/177	L-2/E-2	32	TL	17.00/2.0	11500/7300	6.5/5.25	10/50
20.5R25	BXDN	★★	193/177	L-3/E-3	31	TL	17.00/2.0	11500/7300	6.5/5.25	10/50
20.5R25	MWS+	★★	193	L-5	78	TL	17.00/2.0	11500	6.5	10
20.5R25	SMS+	★★	193	L-5S	72	TL	17.00/2.0	11500	6.5	10

20.5R25	LCHS+	★★	193	L-5	72	TL	17.00/2.0	11500	6.5	10
20.5R25 (525/80R25)	B05N	★★★★	179	E-2	31	TL	17.00/2.0	7750	10	70
21.00R33	B06S	★★	200	E-4P	54	TL	15.00/3.0	14000	7	50
21.00R35	BDRS	★★	201	E-4	54	TL	15.00/3.0	14500	7	50
21.00R35	B04S2	★★	201	E-4	52	TL	15.00/3.0	14500	7	50
23.5R25	B01N	★★	201/185	L-3/E-3	34	TL	19.00/2.5	14500/9250	6.5/5.25	10/50
23.5R25	B01NL	★★	201	L-3	34	TL	19.00/2.5	14500	6.5	10
23.5R25	B02N	★★	201/185	L-3/E-3	34	TL	19.50/2.5	14500/9250	6.5/5.25	10/50
23.5R25	BWYN	★★	201/185	L-2/E-2	34	TL	19.50/2.5	14500/9250	6.5/5.25	10/50
23.5R25	BWYNL	★★	201/185	L-2/E-2	34	TL	19.50/2.5	14500/9250	6.5/5.25	10/50
23.5R25	SNOWMASTER	★★	201/185	L-2/E-2	34	TL	19.50/2.5	14500/9250	6.5/5.25	10/50
23.5R25	BXDN	★★	201/185	L-3/E-3	42.5	TL	19.50/2.5	14500/9250	6.5/5.25	10/50
23.5R25	BDTS	★★	185B	E-4	48	TL	19.50-2.5	9250	5.25	50
23.5R25	MWS+	★★	201	L-5	87	TL	19.50/2.5	14500	6.5	10
23.5R25	MWS	★★	201	L-4	51	TL	19.50/2.5	14500	6.5	10
23.5R25	SMS+	★★	201	L-5	83	TL	19.50/2.5	14500	6.5	10
23.5R25	LCHS+	★★	201	L-5	78	TL	19.50/2.5	14500	6.5	10
24.00R35	BDRS	★★	209	E-4	58	TL	17.00/3.5	18500	7	50
24.00R35	B04S2	★★	209	E-4	58	TL	17.00/3.5	18500	7	50
24.00R35	B04S									
26.5R25	B01N	★★	209/193	L-3/E-3	37	TL	22.00/3.0	18500/11500	6.5/5.25	10/50
26.5R25	B01NL	★★	209	L-3	37	TL	22.00/3.0	18500	6.5/5.25	10
26.5R25	B02N	★★	209/193	L-3/E-3	37	TL	22.00/3.0	18500/11500	6.5/5.25	10/50
26.5R25	BWYN	★★	209/193	L-2/E-2	37	TL	22.00/3.0	18500/11500	6.5/5.25	10/50
26.5R25	BXDN	★★	209/193	L-3/E-3	45	TL	22.00/3.0	18500/11500	6.5/5.25	10/50
26.5R25	BDTS	★★	193B	E-4	52	TL	22.00-3.0	11500	5.25	50
26.5R25	MWS+	★★	209	L-5	96	TL	22.00/3.0	18500	6.5	10
26.5R25	MWS	★★	209	L-4	60	TL	22.00/3.0	18500	6.5	10
26.5R25	SMS+	★★	209	L-5S	90	TL	22.00/3.0	18500	6.5	10
26.5R25	LCHS	★★	209/193	L-4/E-4	57	TL	22.00/3.0	18500/11500	6.25/5.25	10/50
26.5R25	LCHS+	★★	209	L-5	87	TL	22.00/3.0	18500	6.5	10
29.5R25	B02N	★★	216/200	L-3/E-3	43.5	TL	25.00/3.5	22400/14000	6.5/5.25	10/50
29.5R25	BWYN	★★	216/200	L-2/E-2	43.5	TL	25.00/3.5	22400/14000	6.5/5.25	10/50

29.5R25	BXDN	★★	216/200	L-3/E-3	48	TL	25.00/3.5	22400/14000	6.5/5.25	10/50
29.5R25	BDTS	★★	200B	E-4	57	TL	25.00-3.5	14000	5.25	50
29.5R25	MWS+	★★	216	L-5	104	TL	25.00/3.5	22400	6.5	10
29.5R25	MWS	★★	216	L-4	66	TL	25.00/3.5	22400	6.5	10
29.5R25	SMS+	★★	216	L-5S	100	TL	25.00/3.5	22400	6.5	10
29.5R25	LCHS+	★★	216	L-5	95	TL	25.00/3.5	22400	6.5	10
29.5R29	B02N	★★	218/202	L-3/E-3	43.5	TL	25.00/3.5	23600/15000	6.5/5.25	10/50
29.5R29	BDTS	★★	202B	E-4	57	TL	25.00-3.5	15000	5.25	50
29.5R29	MWS+	★★	218	L-5	104	TL	25.00/3.5	23600	6.5	10
29.5R29	SMS+	★★	218	L-5	100	TL	25.00/3.5	23600	6.5	10
29.5R29	LCHS	★★	218/202	L-4/E-4	60	TL	25.00/3.5	23600/15000	6.25/5.25	10/50
29.5R29	LCHS+	★★	218	L-5	95	TL	25.00/3.5	23600	6.5	10
35/65R33	MWS+	★★	224	L-5	97	TL	28.00/3.5	28000	6.5	10
35/65R33	MWS	★★	224	L-4	62.5	TL	28.00/3.5	28000	6.5	10
35/65R33	SMS+	★★	224	L-5	97	TL	28.00/3.5	28000	6.5	10
35/65R33	LCHS	★★	224/207	L-4/E-4	62.5	TL	28.00/3.5	28000/17500	6.25/5.25	10/50
35/65R33	LCHS+	★★	224	L-5	97	TL	28.00/3.5	28000	6.5	10
600/65R25	B02S	★★	187/178	L-3/E-3	35.5	TL	19.50/2.5	9750/7500	4.75/4.25	10/50
650/65R25	B02S	★★	193/180	L-3/E-3	38.5	TL	19.50/2.5	11500/8000	4.75/4.25	10/50
750/65R25	B02S	★★	202/190	L-3/E-3	44.5	TL	24.00/3.0	15000/10600	4.75/4.25	10/50
850/65R25	B02S	★★	207/196	L-3/E-3	48.5	TL	27.00/3.5	17500/12500	4.75/4.25	10/50
875/65R29	B02S	★★	214/203	L-3/E-3	52.5	TL	28.00/3.5	21200/15500	4.75/4.25	10/50
875/65R29	BDTS									
27.00R49	HLG03	★★	223	E-4	61	TL	19.50/4.0	27250	7.0	50
27.00R49	HLG01	★★	223	E-4	58	TL	19.50/4.0	27250	7.0	50
30.00R51	HLG06	★★	230	E-4	64	TL	22.00/4.5	33500	7.0	50
30.00R51	HLG05									
33.00R51	HLG01									
33.00R51	HLG06	★★	235	E-4	70	TL	24.00/5.0	38750	7.0	50
36.00R51	HLG01									
36.00R51	HLG02									
36.00R51	HLG06	★★	241	E-4	78	TL	26.00/5.0	46250	7.0	50
37.00R57	HLG01	★★	246	E-4	89	TL	27.00/6.0	51500	7.0	50
40.00R57	HLG03	★★	250	E-4	93	TL	29.00/6.0	60000	7.0	50